

DIGITAL DOOR LOCK

GPC1 Touchpad & RF card door lock type

COLOR	Silver	Black	Chrome
	The sales		

Product Features



- ★ A touch sensor type, ultra-slim and noble design
 It does not require you any motion as to lift up the product's cover.
 Just gently touch your password on the pad.
- → RF card keys (13.56MHz, ISO 14443A Type)
 If your card has RF function (13.56MHz, ISO 14443A Type),
 then you can register it as your card to use the system.
- → Can support operational modes suitable for various users environments You may set the desirable operation mode for your environment whether it is a general house or office.
- → Fire detection alarm sounds and automatic release of the locking device It includes the fire detection alarm function. If heat above 60 degrees celsius is detected, then the alarm sound will be generated and the door lock will automatically release the locking function.
- Automatic locking function

It is automatically locked after you close the door. You will never leave your home without locking the door.

Antitheft and double locking

If you set the double locking function when you are inside, then no one can open the door from the outside. To the contrary, if you set the antitheft function from the outside, an alarm sound will occur as they open the door from the inside.

Override emergency cylinder keys

User can use an override cylinder keys in case of a circuit trouble.

Product Specifications

Sizes	Inner device (mm)	157(W) x 90(H) x 37(D)		
	Outer device (mm)	70(W) x 150(H) x 19(D)		
Material	Inner device	Aluminum die casting, Zinc, ABS		
	Outer device	Aluminum die casting		
Temperature of Use	-20°C ~ 55°C	Net Weight	1.5Kg	
Voltage of Use	Rate voltage 6[V] (4 pcs. of 1.5[V] AA type alkaline batteries)			
User	Maximum 20 users can be use			





Emergency key



Made in South Korea and Distributed in Thailand by