

DIGITAL DOOR LOCK

<u>GPC2</u> Touchpad & RF card Mortise door lock

Product Features

A touch sensor type, ultra-slim and noble design

It does not require you any motion as to lift up the product's cover. Just gently touch your password on the pad.

3 ways unlocked

RF card key (13.56MHz metro card alike), Password & Manual keys

🔹 Voice guidance

It supports announcement coming out by voice guidance so that user can use more convenient and easy.

Fire detection alarm and automatically unlocked

It includes a fire detector. If inside heat around 60 °C or 140 $^\circ$ F are detected, then the alarm sound will be generated and the lock will be automatically unlocked.

Password leakage protection

Press a lot of unspecified number at random before password so that password can be concealed. Password can be set by 4~12 digits number.

Prevents high-voltage electric shock

High-endurance circuit safe technology adopted against high-voltage electrical shocks even up to 30,000(v).

Double locking & Anti-panic action from inside

If you set the double locking function when you are inside, then no one can open the door from the outside. The door can be opened only by turning the handle from inside even double locked.

Forcible invasion alarm function

If someone forcefully attempts to open the door or damage to the lock, then alarm sound will be generated.

Automatic lock or Manual lock

It is automatically locked after you close the door. You will never leave your home without locking the door. User can be set manual locking mode also.

Emergency manual keys

User can use a manual in case of a circuit trouble or no batteries.

Certificated KPS (Korea Products Safety)

Security and quality guaranteed by international certificates.

Product Specifications

Size	Outer device	283(H)X 78(W) X 27 (D) mm
	Inner device	295(H) X 75 (W) X 35 (D) mm
Material	Outer device	Zinc die casting, Optical acrylic, Incombustible rubber
	Inner device	Aluminum & Zinc die casting, Incombustible ABS resin &rubber
	Mortise case	Galvanized steel case , Zinc die casting deadbolt
RF Card		13.56MHz Metro card alike
Pin Code		4~12 digits number combination
User		Max. 20 RF cards can be registered
Battery		8EA (AA type, Alkaline battery)
		(If use 10 times a day , it will be used about a year)
Door thickness		42 mm~ 55 mm (1.65 inches ~ 2.16 inches)
Working temperature		-15 °C ~ 50 °C (5 °F~ 122°F)
Color		Silver ,Gold

RF Card



Made in South Korea and Distributed in Thailand by

G-Plus Trading Co.,Ltd. 24/33 Moo 6 Bangna-Trad Rd., K.M. 24 Bangsaothong, Samuthprakarn 10540 Tel. (662) 740-1266 Fax. (662) 740-1036 www.g-plus.co.th

Outer

COLOR

Silver

Gold

Inner